



Datasheet: DS-AI8114Z

Product Picture		Hardware		
	Image Sensor	1/1.8" SONY EXMOR Progressive Scan CMOS SENSOR		
	Effective Pixels	2560 * 1440		
	NPU	1.2 Tops		
	Interface			
	Optical lens	Interfaces	-----	
		Iris	-----	
		Focal Length	AF 8-32mm lens + 6mm	
	Audio Talkback	1ch MIC external access, 3.5mm AV interface		
	Audio Output	1ch speaker output, 3.5mm AV interface		
	Network Port	Lan	10/100M BASE-TX, RJ-45 connector	
	RS485	1*RS485 interface		
	Alarm I/O	2ch alarm input, 1ch alarm output		
	Micro SD	Max. 128G		
	Product Features:		Audio&Video encoding	
<ul style="list-style-type: none"> * 1/1.8" SONY Exmor CMOS * 4 Megapixel, 2560 * 1440 * AF 8-32mm + 6mm lens, IR distance 100m * Support protocols: PROFILE S, FTP/RTSP/UPNP etc. * Support Audio I/O, dual Alarm in/ single Alarm in out, RS485, SD card slot(128G), RJ45, DC12V 	Video Compression	H.265/H.264/MJPEG		
			H.265 encoding: Main Profile	
			H.264 encoding: High Profile/Main Profile/Baseline	
	Resolution	Main Stream	2560*1440/1280*720, 1~30fps(adjustable)	
		Sub Stream	1280*720 / 640*480, 1~30fps(adjustable)	
	Video Bitrate	30Kbps~16Mbps, Supports CBR/VBR		
	OSD Settings	Text overlay supported like title, time, date, week, bitrate and etc.		
		OSD location is adjustable		
	Privacy Mask	4 configurable regions		
	Image Orientation	Image Flip and Mirror		
	Auto Image Control Functions	Auto Exposure Control (AEC); Auto White Balance (AWB); Auto Gain Control(AGC)		
	Image Controls	Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-WDR		
	Audio Compression	G.711A/G.711U/G.726		
Two Way Audio	Support			
Application Scenarios:		Data transmission and storage		
Supermarket, hotel, airport, office building etc.	Data storage	Video and Image		
	Recording	Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)		
	Alarm output	FTP, E-mail		
	Network protocols	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP		
Order Type:		Wireless protocols(-W)		
DS-AI8114Z	ONVIF Protocols	PROFILE S		
	Remote View	PC	IE 6.0 above	
		User Access	Maximum 5 users	
Outline Dimension:		General Parameters		
	Environmental Casing	Aluminum Alloy Housing, Indoor and Outdoor Applicable		
	Installation	Wall Mounted		
	Operating Temperature	-10 °C ~ 50 °C		
	Operating Humidity	0% -85% RH		
	Power	DC12V		
	POE	Support		
	Power Consumption	<10W		
	Dimension	352mm(L) * 149mm(W) * 112.5mm(H)		
	Weight	2340g		