


Product Picture:		Hardware		
		Image Sensor	1/1.8" SONY EXMOR Progressive Scan CMOS sensor	
		Effective Pixels	2688×1520	
		Interface		
		Optical lens	Interfaces	§ 14
			Iris	Fixed Iris
			Focal Length	3.6-10mm(Motorized & One Push)
		Audio Talkback	1ch MIC external access, 3.5mm AV interface	
		Audio Output	1ch speaker output, 3.5mm AV interface	
		Network Port	Lan	10/100M BASE-TX, RJ-45 connector
		RS485	1*RS485 interface	
Alarm I/O	2ch alarm input, 1ch alarm output			
Micro SD	Max. 128G			
Product Features:		Audio&Video encoding		
<ul style="list-style-type: none"> ●1/1.8" SONY EXMOR Progressive Scan CMOS sensor ●4.0 Megapixel, 2688×1520 ●3.6-10mm(Motorized & One Push), 3pcs IR Array LED for 30M, IR ON 0.01 Lux, 110dB TWDR ●Support ONVIF Profile S, FTP, RTSP, UPnP etc. ●Support Dual-Stream, Mobile Surveillance, Heartbeat Mechanism, 3D-DNR, Defogging, D-WDR, Lens Correction, Corridor Monitoring etc. ●Built-in MIC, Audio I/O, Dual Alarm In, Single Alarm Out, SD card slot(Max. 128G), RS485, RJ45, DC 12V,POE ●Vandal-proof, Weather-proof, IK10 		Video Compression	H.265/H.264/MJPEG H.265 encoding: Main Profile H.264 encoding: High Profile/Main Profile/Baseline	
		Resolution	Main Stream	2592*1944/1920*1080; 1~30fps(adjustable)
			Sub Stream	1920*1080/640*480; 1~30fps(adjustable)
		Video Bitrate	30Kbps~16Mbps, Supports CBR/VBR	
		OSD Settings	Text overlay supported like title, time, date, week, bitrate and etc. OSD location is adjustable	
		Privacy Mask	4 configurable regions	
		Image Orientation	Image Flip and Mirror	
		Auto Image Control Functions	Auto Exposure Control (AEC); Auto White Balance (AWB); Auto Gain Control(AGC)	
		Image Controls	Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-WDR	
		Others	Anti Fogging/Anti Trembling/IR Detection/IRIS/	
		Audio Compression	G.711A/G.711U/G.726	
		Two Way Audio	Support	
		Application Scenarios:		Data transmission and storage
Supermarket, hotel, airport, office building etc.		Data storage	Video and Image	
		Recording	Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)	
		Alarm output	FTP, E-mail	
		Network protocols	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP	
Order Type:		Wireless protocols(-W) -----		
DS-HD6374ZRH		ONVIF Protocols	PROFILE S	
		Remote View	PC	IE 6.0 above
			Mobile Phone	-----
			User Access	Maximum 5 users
Outline Dimension:		General Parameters		
		Environmental Casing	Aluminum Alloy Housing, Indoor and Outdoor Applicable	
		Installation	Ceiling Mounted & Wall Mounted	
		Operating Temperature	-10 °C ~ 50 °C	
		Operating Humidity	0% -85% RH	
		Power	DC12V ±10%	
		POE	Support	
		Power Consumption	<3.5W, IR ON<9W	
		Dimension	Φ161mmxH115mm	
		Weight	965g	