



SHEN ZHEN DOWSE ELECTRONICS CO.,LTD

Tel: +86-755-29500291 Fax: +86-755-29500213

Add: 3F, 9#BL, JinXiu Science Park, Wuhe Blvd North, Guanhu Town, Longhua District, ShenZhen, China518000

Datasheet: DS-605CV

Product Picture	Hardware	
	■ 2MP,30fps@1920*1080,3.7mm lens,0.005Lux	
	■ Four in one output (AHD、CVI、TVI、CVBS)	
	■ WDR 140dB	
	■ DC 12V ±10%	
size:	technical parameter:	
	Image Sensor	1/2.8"SONY Progressive Scan CMOS SENSOR
	Sensor size	4.9mm(H)×3.7mm(V)
	Effective Pixels	1920*1080
	Minimum illumination	0.005Lux
	S/N	More than 52dB
	Automatic electronic shutter	PAL1/50s-1/10,000s NTSC1/60s-1/10,000s
	BLC	OFF/HLC
Application Scenarios: ATM machines, video conferences and other places	Synchronization	INT
	video output	1.0Vp-p, 75Ω, BNC Connector
	Standard lens/interface	3.7mm
	Day and night conversion	Color to B&W
	Operating temperature	-30℃~+60℃
	Operating Voltage	DC 12V±10%
	Working current	110mA
	Size	L37.4 ×W31.02×H20mm
Model: DS-605CV	Weight	50g
	Material	Zinc alloy