


Datasheet: DS-AI6372ZR

Product Picture



Hardware

| | |
|------------------|--|
| Image Sensor | 1/2.8" SONY EXMOR Progressive Scan CMOS SENSOR |
| Effective Pixels | 1920(H)×1080(V) |
| NPU | 1.2 Tops |

Interface

| | | |
|----------------|---|----------------------------------|
| Optical lens | Interfaces | φ14 |
| | Iris | Fixed Iris |
| | Focal Length | 2.7-13.5mm (Motorized) lens |
| Audio Talkback | 1ch MIC external access, 3.5mm AV interface | |
| Audio Output | 1ch speaker output, 3.5mm AV interface | |
| Network Port | Lan | 10/100M BASE-TX, RJ-45 connector |
| RS485 | 1*RS485 interface | |
| Alarm I/O | 2ch alarm input, 1ch alarm output | |
| Micro SD | Max. 128G | |

Product Features:

- ◎ 1/2.8" SONY Exmor CMOS
- ◎ 2.0 Megapixel, 30fps@1920*1080
- ◎ 2.7-13.5mm (Motorized) lens, IR distance 30m, 40dB TWDR
- ◎ Support protocols: PROFILE S, GB/T28181, FTP/RTSP UPNP etc.
- ◎ Support three Stream, Mobile Surveillance, Heartbeat Mechanism, 3D-DNR, Defogging, D-WDR, Lens Correction, Corridor Monitoring etc.
- ◎ Built-in Mic, support Audio I/O, dual Alarm in/ single Alarm in out, RS485, SD card slot (128G), RJ45, DC12V

Optional

Face capture algorithm (support face capture function, support for detecting, tracking, capturing, and screening of moving faces, outputting superior face capture)

Audio&Video encoding

| | | |
|------------------------------|---|--|
| Video Compression | H.265/H.264/MJPEG | |
| | H.265 encoding: Main Profile | |
| | H.264 encoding: High Profile/Main Profile/Baseline | |
| Resolution | Main Stream | 1920*1080/1280*720; 1~30fps(adjustable) |
| | Sub Stream | 704*576/640*480/640*352/320*240; 1~30fps(adjustable) |
| Video Bitrate | 30Kbps~16Mbps, Supports CBR/VBR | |
| OSD Settings | Text overlay supported like title, time, date, week, bitrate and etc. OSD location is adjustable | |
| Privacy Mask | 4 configurable regions | |
| Image Orientation | Image Flip and Mirror | |
| Auto Image Control Functions | Auto Exposure Control (AEC); Auto White Balance (AWB); Auto Gain Control(AGC) | |
| Image Controls | Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-WDR | |
| Others | Anti Fogging/Anti Trembling/IR Detection/IRIS/ | |
| Audio Compression | G.711A/G.711U/G.726 | |
| Two Way Audio | Support | |

Application Scenarios:

Supermarket, hotel, airport, office building etc.

Data transmission and storage


| | |
|-------------------|--|
| Data storage | Video and Image |
| Recording | Auto recording and manual recording (motion & sensor alarm recording, scheduled recording) |
| Alarm output | FTP, E-mail |
| Network protocols | TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP |

Order Type:

DS-AI6372ZR

| | | |
|------------------------|--------------|------------------------------------|
| Wireless protocols(-W) | ----- | |
| ONVIF Protocols | PROFILE S | |
| Remote View | PC | IE 6.0 above, Firefox, Google etc. |
| | Mobile Phone | ----- |
| | User Access | Maximum 5 users |

Outline Dimension:



General Parameters

| | |
|-----------------------|---|
| Environmental Casing | Aluminum Alloy Housing, Indoor and Outdoor Applicable |
| Installation | Ceiling Mounted & Wall Mounted |
| Operating Temperature | -10 °C ~ 50 °C |
| Operating Humidity | 0% -85% RH |
| Power | DC12V |
| POE | Support |
| Power Consumption | <3.5W |
| Dimension | 161mm(Φ)x115mm(H) |
| Weight | 965g |