

Product Picture: 	Hardware	
Product Features: <ul style="list-style-type: none"> ●1/1.8" SONY EXMOR Progressive Scan CMOS SENSOR ●2.0 Megapixel, 30fps@1920*1080 ●3.6-10mm(Motorized & One Push), 3pcs IR Array LED for 30M, IR ON 0.001 Lux, 140dB TWDR ●Support ONVIF Profile S, FTP, RTSP, UPnP etc. ●Support Dual-Stream, Mobile Surveillance, Heartbeat Mechanism, 3D-DNR, Defogging, D-WDR, Lens Correction, Corridor Monitoring etc. ●Built-in MIC, Audio I/O, Dual Alarm In, Single Alarm Out, SD card slot(Max. 128G), RS485, RJ45, DC 12V, POE 	Audio&Video encoding	
Application Scenarios: Supermarket, hotel, airport, office building etc.	Data transmission and storage	
Order Type: DS-HD6362ZRH	Wireless protocols(-W) -----	
Outline Dimension: 	General Parameters	
Image Sensor	1/1.8" SONY EXMOR Progressive Scan CMOS SENSOR	
Effective Pixels	1920(H)×1080(V)	
Interface		
Optical lens	Interfaces	\$ 14
	Iris	Fixed Iris
	Focal Length	3.6-10mm (Motorized & One Push)
Audio Talkback	1ch MIC external access, 3.5mm AV interface	
Audio Output	1ch speaker output, 3.5mm AV interface	
Network Port	Lan	10/100M BASE-TX, RJ-45 connector
RS485	1*RS485 interface	
Alarm I/O	2ch alarm input, 1ch alarm output	
Micro SD	Max. 128G	
Video Compression	H.265/H.264/MJPEG	
	H.265 encoding: Main Profile	
	H.264 encoding: High Profile/Main Profile/Baseline	
Resolution	Main Stream	1920*1080/1280*720; 1~30fps(adjustable)
	Sub Stream	704*576/640*480/640*352/320*240; 1~30fps(adjustable)
Video Bitrate	30Kbps~16Mbps, Supports CBR/VBR	
OSD Settings	Text overlay supported like title, time, date, week, bitrate and etc.	
	OSD location is adjustable	
Privacy Mask	4 configurable regions	
Image Orientation	Image Flip and Mirror	
Auto Image Control Functions	Auto Exposure Control (AEC); Auto White Balance (AWB); Auto Gain Control(AGC)	
Image Controls	Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-WDR	
Others	Anti Fogging/Anti Trembling/IR Detection/IRIS/	
Audio Compression	G.711A/G.711U/G.726	
Two Way Audio	Support	
Data storage	Video and Image	
Recording	Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)	
Alarm output	FTP, E-mail	
Network protocols	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP	
ONVIF Protocols	PROFILE S	
Remote View	PC	IE 6.0 above
	Mobile Phone	-----
	User Access	Maximum 5 users
Environmental Casing	Aluminum Alloy Housing, Indoor Applicable	
Installation	Ceiling Mounted & Wall Mounted	
Operating Temperature	-10 °C ~ 50 °C	
Operating Humidity	0% -85% RH	
Power	DC12V ±10%	
POE	Support	
Power Consumption	<3.5W, IR ON<9W	
Dimension	Φ143xH114mm	
Weight	655g	